

Technical Specifications

Model a625d	PL331AA
Processor & Speed	2.8 GHz/400 Intel® Pentium® 4 Processor – PGA478
Chipset	Intel® 865G
Motherboard	Cobra-GL6E (4PSD-LA)
RAM	256/3200 MB 400DDR SDRAM (runs@266MHz)
Maximum	3 GB
Sockets	Four 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	Three
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	16KB Data Cache + Trace Cache L1, 256 KB L2 Integrated on Processor module
Hard Drive	40 GB (5400 RPM)
Optical Drive	DVD-ROM Drive: DVD (16x max.) / CD-ROM (48x max.)
Average Random Access	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	None
Video Graphics	Intel® Extreme Graphics
Controller	Integrated w/865G Chipset
Video Memory	Dynamic up to 64MB UMA
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Panther-Lite, 250HV PSU
USB Interface Specification	USB 2.0
External I/O Rear Connectors	4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
External I/O Front Connectors	2= USB, 1= 1394, Line In, Microphone, Headphone
Expansion Slots (Total)	3= PCI
Expansion Slots (FREE)	3= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2004

This information is subject to change without notice and is provided "as is" with no warranty.

Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.